



HIGH SPECIFICATION PRODUCTS

Product Data Sheet

HSP-RT-AC Activated Carbon Impregnated Reticulated Foam

<i>Grade</i>	<i>Issue Number</i>	<i>Date</i>
HSP-RT-AC	1	1 st December 2010

Description: 20, 30 or 45ppi reticulated open cell foam post treated with Activated carbon

Uses: Fume absorption; solder fume removal, ozone removal. Aquatic filters.

<i>HSP-RT</i>	<i>20-AC50</i>	<i>30-AC75</i>	<i>45-AC100</i>
---------------	----------------	----------------	-----------------

Foam Type	Polyether based Polyurethane impregnated with activated carbon flexible latex		
------------------	--	--	--

Density	33 Kg/m³	37 Kg/m³	42 Kg/m³
----------------	----------------------------	----------------------------	----------------------------

Pore Size	20ppi	30ppi	45ppi
------------------	--------------	--------------	--------------

Density of Carbon	5 Kg/m³	7.5 Kg/m³	10 Kg/m³
--------------------------	---------------------------	-----------------------------	----------------------------

Weight Of Carbon (%)	16	20	24
-----------------------------	-----------	-----------	-----------

CTC Adsorption	3.2 Kg/m³	6.0 Kg/m³	10.9 Kg/m³
-----------------------	-----------------------------	-----------------------------	------------------------------

Colour	Black		
---------------	--------------	--	--

Additional Notes:
All HSP Rigid grades are RoHS compliant

The data contained herein is believed to be accurate at time of issue, and is published in good faith. However, H.S.P.Ltd reserves the right to amend product data without prior notification. H.S.P.Ltd can assume no liability for results obtained or damages incurred through the application of the data and tests presented.